OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Reviewed on 05/23/2017

1 Identification

- · Product Identifier
- Trade name: Marble
- Relevant identified uses of the substance or mixture and uses advised against: Relevant identified uses include commercial, residential and institutional applications.
- · Product Description Natural Stone Products
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier: AlysEdwards Tile & Stone® 1123 Warner Ave. Tustin, CA 92705 714-917-6720
 Emergency telephone number: Eric Jessen Human Resources Director 559-476-5183

2 Hazard(s) Identification

· Classification of the substance or mixture:



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements:
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms:



· Signal word: Danger

Hazard-determining components of labeling:
 Quartz (SiO2)
 Feldspar
 Hazard statements:

H320 Causes eye irritation. H350 May cause cancer.

Reviewed on 05/23/2017

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

H335 May cause respiratory irritation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements:

· Precautionary statements:			
Obtain special instructions before use.			
Do not handle until all safety precautions have been read and understood.			
Do not breathe dust/fume/gas/mist/vapors/spray.			
Avoid breathing dust/fume/gas/mist/vapors/spray.			
Wash thoroughly after handling.			
Do not eat, drink or smoke when using this product.			
Use only outdoors or in a well-ventilated area.			
Wear protective gloves/protective clothing/eye protection/face protection.			
IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
3 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if			
present and easy to do. Continue rinsing.			
IF exposed or concerned: Get medical advice/attention.			
Call a POISON CENTER/doctor if you feel unwell.			
Get medical advice/attention if you feel unwell.			
If eye irritation persists: Get medical advice/attention.			
Store in a well-ventilated place. Keep container tightly closed.			
Store locked up.			
Dispose of contents/container in accordance with local/regional/national/international regulations.			

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- 2.3 % of the mixture consists of component(s) of unknown toxicity.
- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

• NFPA ratings (scale 0 - 4)



Reactivity –

HMIS-ratings (scale 0 - 4)

HEALTH*3FIRE0Fire = 0REACTIVITYPhysical Hazard = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

 Dangerous Compon 	ents:	
CAS: 1317-65-3	Calcium Carbonate	60-90%
CAS: 14808-60-7	Quartz (SiO2)	15-35%
RTECS: VV 7330000	♦ Carc. 1A, H350; STOT RE 1, H372; ♦ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	-
CAS: 68476-25-5	Feldspar	5-10%
CAS: 12001-26-2	Mica	≤ 2.5%

(Contd. on page 3)

Reviewed on 05/23/2017

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

· Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

• Description of first aid measures:

General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- After inhalation: If a cough develops the individual should seek medical attention.
- · After skin contact:
- Wash with soap and water.
- If skin irritation occurs, consult a doctor.
- · After eye contact:
- Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Not applicable for intact natural stone products.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed:

Quartz: Can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death; inhaled from occupational sources is classified as carcinogenic to humans. Some studies show in workers exposed to respirable quartz excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease, chronic bronchitis and emphysema.

Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media:
- Suitable extinguishing agents: None required Non-flammable
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters:
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

· Additional information: This product will not burn.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Avoid creating excessive dust.
- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Clean up dust with a vacuum system with a High-efficiency particulate (HEPA) air filter vacuum or damp sweeping.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

· Protective Action Criteria for Chemicals

· PAC-1:		
14808-60-7	Quartz (SiO2)	0.075 mg/m3
12001-26-2	Mica	9 mg/m3
1345-25-1	iron oxide	45 mg/m3
· PAC-2:		
14808-60-7	Quartz (SiO2)	33 mg/m3
12001-26-2	Mica	99 mg/m3
1345-25-1	iron oxide	500 mg/m3
· PAC-3:		
14808-60-7	Quartz (SiO2)	200 mg/m3
12001-26-2	Mica	590 mg/m3
1345-25-1	iron oxide	3,000 mg/m3

7 Handling and Storage

· Handling

Precautions for safe handling:

When cutting, grinding or removing, use equipment with integral dust collection and/or use local exhaust ventilation. Use wet cutting methods to reduce generation of dust. Use respiratory protection in the absence of effective engineering controls.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities:

· Storage

- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility:

Do not store near acids. If natural stone products contact some acids, damage/discoloration to the surface may occur.

- Further information about storage conditions: Shelf life is unlimited.
- Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

- Control parameters:
- Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

1317-65-3 Ca	Icium Carbonate
	Short-term value: 5 mg/m³ Long-term value: 10 mg/m³
	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³ espirable dust

(Contd. on page 5)

Reviewed on 05/23/2017

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

OSHA Short-term value: 5 mg/m³ Long-term value: 15 mg/m³ Short-term value: 5 mg/m³ OSHA TWA Long-term value: 15 mg/m³ espirable fraction 14808-60-7 Quartz (SiO2) PEL see Quartz listing Long-term value: 0.05* mg/m³ REL *respirable dust; See Pocket Guide App. A TLV Long-term value: 0.025* mg/m³ *as respirable fraction 12001-26-2 Mica PEL Long-term value: 20 mppcf ppm <1% crystalline silica Long-term value: 3* mg/m³ REL *respirable dust; containing < 1% quartz</p> TLV Long-term value: 3* mg/m³ *as respirable fraction

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

• Exposure controls:

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS. Where acceptable concentrations cannot be maintained by general mechanical ventilation, local exhaust ventilation is recommended.

· Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

Use of a properly fitted NIOSH/MSHA approved particulate respirator is recommended when cutting natural stone products for installation or during the removal of installed product.

Protection of hands:



Protective gloves

Cotton or leather work gloves should be worn when cutting this product to minimize skin exposure to dust and/ or cuts.

- · Material of gloves: Not applicable
- · Penetration time of glove material: Not applicable.
- · Eye protection:

Use dust-proof goggles or safety glasses with side shields. Contact lenses may absorb irritants. Do not wear contact lenses in work areas.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

9 Physical and Chemical Properties

· Information on basic physical and chemical properties

Reviewed on 05/23/2017

• General Information • Appearance:		
Form:	Solid	
Color:	Various colors	
· Odor:	Odorless	
· Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. Not determined.	
· Flash point:	None	
· Flammability (solid, gaseous):	Not determined.	
 Ignition temperature: 	Not applicable	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not self-igniting.	
• Danger of explosion:	Product does not present an explosion hazard.	
• Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure:	Not applicable.	
 Density: Relative density: Vapor density: Evaporation rate: 	Not determined. Not applicable. Not applicable.	
 Solubility in / Miscibility with: Water: 	Insoluble.	
Partition coefficient (n-octanol/water): Not determined.		
 Viscosity: Dynamic: Kinematic: 	Not applicable. Not applicable.	
 Solvent content: Organic solvents: Other information: 	0.0 % No further relevant information available.	
10 Stability and Reactivity		

· *Reactivity:* No further relevant information available.

· Chemical stability: Stable under normal conditions.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• Possibility of hazardous reactions: No dangerous reactions known.

• Conditions to avoid: Avoid contact with acids (e.g., Hydrochloric, acetic, hydrofluoric, etc.)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

· Incompatible materials:

Contact with fluorine, oxygen dilfuoride, and chlorine trifluoride will cause fire. Avoid contact with acids (e.g., Hydrochloric, acetic, hydrofluoric, etc.) Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological Information

· Information on toxicological effects:

· Acute toxicity:

· LD/LC50 values that are relevant for classification:		
1317-65-3 Calcium Carbonate		
Oral	LD50	6450 mg/kg (Rat)
14808-60-7 Quartz (SiO2)		
Oral	LD50	> 22500 mg/kg (Rat)
Inhalative	LC50/96 hours	1033 mg/l (Trout)
Primary irritant effect:		

Primary irritant effect:

• On the skin: Mild irritant effect.

• On the eye: Irritating effect.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):

"In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicate dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable crystalline silica should be monitored and controlled"

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

14808-60-7 Quartz (SiO2)

• NTP (National Toxicology Program):

14808-60-7 Quartz (SiO2)

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

(Contd. on page 8)

Reviewed on 05/23/2017

K

1

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Reviewed on 05/23/2017

Trade name: Marble

12 Ecological Information

- · Toxicity:
- · Aquatic toxicity:

14808-60-7 Quartz (SiO2)

- EC50 218 mg/l (Green algae)
- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects: No further relevant information available.

3 Disposal Considerations

· Waste treatment methods:

• Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packagings

· Recommendation: Disposal must be made according to official regulations.

rane	nort	Intol	rmation	
	991 L	шы	пецы	

· UN-Number:		
DOT, ADR/ADN, ADN, IMDG, IATA UN proper shipping name:	Non-Regulated Material	
• DOT, ADR/ADN, ADN, IMDG, IATA • Transport hazard class(es):	Non-Regulated Material	
· DOT, ADR/ADN, ADN, IMDG, IATA		
· Class:	Non-Regulated Material	
· Packing group:	-	
· DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material	
· Environmental hazards:	Not applicable.	
 Special precautions for user: 	Not applicable.	
 Transport in bulk according to Annex II of 	of	
MARPOL73/78 and the IBC Code:	Not applicable.	
• UN "Model Regulation":	Non-Regulated Material	
		(Contd. on page 9)

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Reviewed on 05/23/2017

Trade name: Marble

5 Regulatory Information

Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	
Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
TSCA (Toxic Substances Control Act):	
1317-65-3 Calcium Carbonate	
14808-60-7 Quartz (SiO2)	
68476-25-5 Feldspar	
1345-25-1 iron oxide	
California Proposition 65:	
Chemicals known to cause cancer:	
14808-60-7 Quartz (SiO2)	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
New Jersey Right-to-Know List:	
1317-65-3 Calcium Carbonate	
14808-60-7 Quartz (SiO2)	
12001-26-2 Mica	
New Jersey Special Hazardous Substance List:	
14808-60-7 Quartz (SiO2)	CA
Pennsylvania Right-to-Know List:	
1317-65-3 Calcium Carbonate	
14808-60-7 Quartz (SiO2)	
12001-26-2 Mica	
Pennsylvania Special Hazardous Substance List:	
None of the ingredients are listed.	
Carcinogenic categories:	
EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
TLV (Threshold Limit Value established by ACGIH):	
14808-60-7 Quartz (SiO2)	A

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Reviewed on 05/23/2017

Trade name: Marble

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

• Hazard pictograms:



· Signal word: Danger

• *Hazard-determining components of labeling:* Quartz (SiO2) Feldspar

· Hazard statements:

- H320 Causes eye irritation.
- H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements:

	liements.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 05/23/2017 / 3

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 05/23/2017

Trade name: Marble

Reviewed on 05/23/2017

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B Carc. 1A: Carcinogenicity – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 * * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106